

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/051560 A1

(51) International Patent Classification⁷: **B21C 47/12**,
47/34, B65H 54/28

(21) International Application Number:
PCT/EP2004/051744

(22) International Filing Date: 6 August 2004 (06.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI 2003 A 001637 8 August 2003 (08.08.2003) IT

(71) Applicant (for all designated States except US): **DANIELI
& C. OFFICINE MECCANICHE S.P.A.** [IT/IT]; Via
Nazionale 41, I-33042 Buttrio (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BORDIGNON**,
Giuseppe [IT/IT]; Via Roma, 10/2, I-33050 Bicinico (IT).
DE LUCA, **Andrea** [IT/IT]; Via Candotti 61, I-33047
Remanzacco (IT). **POLONI**, **Alfredo** [IT/IT]; Via G.
Paolini 29, I-34070 Fogliano Redipuglia (IT).

(74) Agent: **GERVASI**, **Gemma**; Notarbartolo & Gervasi
S.p.A., Corso di Porta Vittoria 9, I-20122 Milan (IT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

(48) Date of publication of this corrected version:


25 August 2005

(15) Information about Correction:

see PCT Gazette No. 34/2005 of 25 August 2005, Section II

[Continued on next page]

(54) Title: A REELING DEVICE FOR SEMI-FINISHED ROLLED PRODUCTS



(57) Abstract: A device for reeling semi-finished rolled products comprises two sections (1, 2) connected together to form an articulated arm that guides the product (BL) coming out of a rolling mill onto the reel that is being wound. The second section (2), which is closer to the reel, during winding, maintains its own inclination constantly equal to the inclination of the turns of the reel. This enables a considerable reduction of the gap between the adjacent turns and prevention of any overlapping (i.e., climbing on top of one another) between the turns already wound and the turns being distributed on the same layer. Reels that are more compact and have a more precise geometry are thus obtained. Also described is a device (12) for guiding the rolled product (BL) arriving on the reel with greater precision.

WO 2005/051560 A1

WO 2005/051560 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.